

Fuse table 1

Level Microprism 3200 lm - 5200 lm

Maximum loading of automatic of circuit breakers

| Automatic circuit breaker type: | C10 | C13 | C16 | C20 | C25 | B10 | B13 | B16 | B20 | B25 | Inrush current |
|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------------|
| Driver: Xtanium 50W WH 0.7-1.5A 54V TD/Is 230V | | | | | | | | | | | I_{max} time |
| Number of drivers: | 28 | 36 | 46 | 56 | 70 | 17 | 22 | 27 | 34 | 42 | 24,9A 186 μ^* |

* Input voltage 230V, Time measured at 50% Ipeak

Fuse table 2

Level Microprism 2600 lm

Maximum loading of automatic of circuit breakers

| Automatic circuit breaker type: | C10 | C13 | C16 | C20 | C25 | B10 | B13 | B16 | B20 | B25 | Inrush current |
|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------------|
| Driver: Xtanium 36W WH 0.3-1A 54V TD/Is 230V | | | | | | | | | | | I_{max} time |
| Number of drivers: | 33 | 43 | 54 | 67 | 83 | 20 | 26 | 32 | 40 | 50 | 20,4A 195 μ^* |

* Input voltage 230V, Time measured at 50% Ipeak