

Fuse table

Plain 600 15W, 300 12W DALI

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 17W 250-700mA O4A SR PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	36	50	60	76		22	30	36	46		18 A 140μ*

* Input voltage 230V, Time measured at 50% Ipeak

[Plain 600 28W DALI >](#)

[Plain 300 21W DALI >](#)

ateljé Lyktan

Plain 600 28W DALI

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 45W 500-1400mA O4A SR PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	21	30	36	46		13	18	22	28		28 A 195µ*

* Input voltage 230V, Time measured at 50% Ipeak

Plain 300 21W DALI

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 25W 350-1050mA one4all SR PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	31	40	51	66		19	24	31	40		25 A 141µ*

* Input voltage 230V, Time measured at 50% Ipeak